

MATERIAL SAFETY DATA SHEET

SECTION I: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: **PRO FOAM SOFT COMPONENT "A"**
PRODUCT USE: Flexible Polyurethane Foam for Cushion

COMPANY: Motion Picture F/X Company
2923 Thornton Ave Burbank, CA 91504
(818) 563-2366 (Tel)
(818) 563-2389 (Fax)
info@motionpicturefx.com

EMERGENCY PHONE: In the event of a leak, fire or medical emergency involving humans and animals call **INFOTRAC 1-800-535-5053** 24 hours per day, 7 days a week. or +1-352-323-3500 (outside the US.)

SECTION II: COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT(S)	% (w/w)	ACGIH TLV	CAS NO.
Diphenylmethane - Diisocyanate (polymeric MDI)	~40	Not Listed	9016-87-9
CONTAINS 4,4'-Diphenylmethane (4,4') (approx. 45%)- Modified Diphenylmethane Diisocyanate -	~40	0.005 ppm	101-68-8
MDI ISOMERS/OLIGOMERS -		0.005 ppm	101-68-8
		Not Listed	9016-87-9
Cyclopentane -	~ 2	600 ppm	287-92-3

SECTION III: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Health Hazards: Irritating to eyes, respiratory system and skin. Inhalation at levels above the occupational exposure limit could cause respiratory sensitization. Risk of serious damage to respiratory system. The onset of respiratory symptoms may be delayed for several hours after exposure. A hyper-reactive response to even minimal concentrations of MDI may develop in sensitized persons. Sensitized persons should not be exposed to any mixture containing un-reacted MDI.

Physical Hazards: Reacts slowly with water to produce carbon dioxide, which may rupture closed containers. This reaction accelerates at higher temperatures.

Appearance: Dark brown liquid

Odor: Slightly musty

Read the entire MSDS for a more thorough evaluation of the hazards

SECTION IV: FIRST AID MEASURES

GENERAL: In case of accident or if you feel unwell, seek medical advice IMMEDIATELY (show the label or MSDS where possible).

Inhalation: Remove patient from exposure, keep warm and at rest. Obtain medical attention. Treatment is symptomatic for primary irritation or difficulty in breathing. If breathing is labored, oxygen should be administered by qualified personnel. Apply artificial respiration if breathing has ceased or shows signs of failing.

Skin Contact: Remove contaminated clothing. Wash affected areas thorough with soap and water. If irritation, redness, or a burning sensation develops and persists, obtain medical advice. Contaminated clothing should be thoroughly cleaned before reuse.

Eye Contact: Immediately flush eyes with running water for a minimum of 15 minutes. Hold eyelids open during flushing. If irritation persists, repeat flushing. Obtain medical attention IMMEDIATELY.

Ingestion: Do NOT induce vomiting. Provided the patient is conscious, wash out mouth with water then give 1 or 2 glasses of water to drink. Refer person to medical personnel for immediate attention.

Note to Physicians: Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.

SECTION V: FIRE-FIGHTING MEASURES

Fire and Explosion Hazards: Containers may burst under intense heat. Due to reaction with water, a hazardous build-up of pressure could result if contaminated containers are re-sealed.

Extinguishing Media: Carbon dioxide, dry chemical, or appropriate foam. If water is used, very large quantities are required. Reaction between water and hot isocyanate may be vigorous. Contain run-off water with temporary barriers.

Fire-Fighting Procedures: As appropriate for surrounding materials/equipment.

Fire-Fighting Protective Equipment: Use self-contained breathing apparatus and full protective clothing (Bunker gear).

Flash Point: 425°F (218°C)

Flammable Limits (Lower): Not available.

Flammable Limits (Upper): Not available.

Auto Ignition Temperature: 240°C (464°F) (4,4'-Diphenylmethane Diisocyanate)

Decomposition Temperature: Not available.

Rate of Burning: Not available.

Explosive Power: None.

Sensitivity to Mechanical Impact: None.

Sensitivity to Static Discharge: None.

Combustion Products: Carbon monoxide, carbon dioxide, nitrogen oxides and some HCN.

SECTION VI: ACCIDENTAL RELEASE MEASURES

Spills, Leaks, or Releases: People dealing with major spillages should wear full protective clothing including full air supplied respirator. Evacuate the area. Prevent further leakage, spillage or entry into drains.

Contain and absorb large spillages onto an inert, non-flammable absorbent carrier (such as earth or sand. Shovel into open-top drums or plastic bags for further decontamination, if necessary. Wash the spillage area clean with liquid decontaminant. Test atmosphere for MDI. Neutralize small spillages with decontaminant. Remove and properly dispose of residues. Notify applicable government authorities if release is reportable. The CERCLA RQ for MDI is 5,000 lbs (see CERCLA in Section 15).

Preparation of Decontamination Solution: Prepare a decontamination solution of 0.2-0.5% liquid detergent and 3-8% concentrated ammonium hydroxide in water (5-10% sodium carbonate may be substituted for the ammonium hydroxide).

Use of Decontamination Solution: Allow deactivated material to stand for at least 30 minutes before shoveling into drums. Do not tighten the bungs. Mixing with wet earth is also effective, but slower.

SECTION VII: HANDLING AND STORAGE

Handling: Avoid personal contact with the product or reaction mixture. Use only with adequate ventilation to ensure that the occupational exposure limit is not exceeded. The efficiency of the ventilation system must be monitored regularly because of the possibility of blockage. Avoid breathing aerosols, mists and vapors. When the product is sprayed or heated, an approved MSHA/NIOSH positive-pressure, supplied air respirator may be required.

Storage Requirements: Keep containers properly sealed and when stored indoors, in a well ventilated area. Keep contents away from moisture. Due to reaction with water, producing CO₂ gas, a hazardous build-up of pressure could result if contaminated containers are re-sealed. Do not reseal contaminated containers. Uncontaminated containers, free of moisture, may be resealed only after placing under a nitrogen blanket. Do not store in containers made of copper, copper alloys or galvanized surfaces.

Storage Temperature: Ideal storage temperature is 16 - 38°C (60 - 100°F).

Keeps stocks of decontaminant (See Section VI) readily available.

SECTION VIII: EXPOSURE CONTROLS/PERSONAL PROTECTION

Preventative Measures:

Conditions of use, adequacy of engineering or other control measures, and actual exposures will dictate the need for specific protective devices at your workplace.

Engineering Controls: Use local exhaust ventilation to maintain airborne concentrations below the TLV. Suitable respiratory equipment should be used in cases of insufficient ventilation or where operational procedures demand it. For guidance on engineering control measures refer to the ACGIH publication "Industrial Ventilation".

Personal Protective Equipment:

Eye Protection: Chemical safety goggles. If there is a potential for splashing, use a full face shield.

Skin Protection: The following protective materials are recommended: Gloves - neoprene, nitrile rubber, butyl rubber. Thin latex disposable gloves should be avoided for repeated or long term use.

Protective clothing should be selected and used in accordance with "Guidelines for the Selection of Chemical Protective Clothing" published by ACGIH.

Respiratory Protection: Use an approved NIOSH/MSHA positive pressure air-supplied respirator equipped with a full face piece, or an air-supplied hood, if airborne concentrations exceed or are expected to exceed the occupational exposure standard. Air purifying (cartridge type) respirators are not approved for protection against diisocyanates.

Exposure Guidelines:

Medical supervision of all employees who handle or come in contact with respiratory sensitizers is recommended. Persons with respiratory problems including asthmatic-type conditions, chronic bronchitis, other chronic respiratory diseases or recurrent skin eczema or skin allergies should be evaluated for their suitability of working with this product. Once a person is diagnosed as sensitized, no further exposure to the material that caused the sensitization should be permitted.

Hazardous Ingredient(s):

4,4'-Diphenylmethane Diisocyanate:

ACGIH TLV	0.005 ppm (8-hour, 40 hours/week)
OSHA PEL CEILING	0.02 ppm
NIOSH REL/TWA	0.005 ppm (10-hour, 40 hours/week)
NIOSH REL/CEILING	0.02 ppm (10-minute)

Note: The Occupational Exposure Limits listed for isocyanates do not apply to previously sensitized individuals.

SECTION IV: PHYSICAL AND CHEMICAL PROPERTIES

Alternate Name(s): Polymeric MDI.

Chemical Name: Not applicable (mixture)

Chemical Family: Diisocyanate.

Molecular Formula: Not applicable (mixture).

Appearance: Dark brown liquid.

Odor: Slightly musty.

Odor Threshold: 4 mg/m³ (4,4'-Diphenylmethane Diisocyanate) ~ 400 ppb.

pH: Not applicable.

Flash Point: 425°F (218°C).

Vapor Pressure (mm Hg at 20°C): Approx. 4×10^{-6} .

Vapor Density (Air=1): 8.5 approx.

Boiling Point: Not applicable.

Melting Point: Not applicable.

Solubility (Water): (Reacts with water).

Solubility (Other): Soluble in most organic solvents.

Specific Gravity: 1.24 approx. (at 25°C).

Evaporation Rate: Not available.

SECTION X: STABILITY AND REACTIVITY

Hazardous Decomposition Products: Highly unlikely under normal industrial use. See Section V.

Chemical Stability: Stable at room temperature.

Conditions to Avoid: Avoid high temperatures. Avoid freezing.

Incompatibility with other substances: This product will react with any materials containing active hydrogens such as water, alcohol, amines, bases and acids. The

reaction with water is very slow under 50°C(122°F) but accelerated at higher temperatures.

Hazardous Polymerization: Polymerization may occur at elevated temperatures in the presence of alkalies, tertiary amines and metal compounds.

SECTION XI: TOXICOLOGICAL INFORMATION

Polymeric MDI:

Oral LD50 (rat) > 5,000 mg/kg
Dermal LD50 (rabbit) > 5,000 mg/kg
Inhalation LC50 (rat) = 490 mg/m³/4 hours (respirable aerosol)

Potential Health Effects:

Inhalation: This product is a respiratory irritant and potential respiratory sensitizer. Inhalation of vapor or aerosol at levels above the occupational exposure limit could cause respiratory sensitization and lung injury. Symptoms may include irritation to the eyes, nose, throat and lungs, possibly combined with dryness of the throat, tightness of chest and difficulty in breathing and/or flu-like symptoms. The onset of the respiratory symptoms may be delayed for several hours after exposure. A hyper-reactive response to even minimal concentrations of MDI may develop in sensitized persons. In a single evaluation of 5 men occupationally exposed to MDI and hydrocarbon solvent vapors under conditions where adequate ventilation or other safety precautions were not used, neuropsychologic findings were attributed to MDI.

Skin Contact: Moderate irritant. Repeated and/or prolonged contact may cause skin sensitization. There is limited evidence from animal studies that skin contact may play a role in respiratory sensitization. These results emphasize the need for protective clothing including gloves to be worn at all times when handling these chemicals or in maintenance work.

Eye Contact: The aerosol, vapor or liquid will irritate human eyes following contact.

Ingestion: Ingestion may cause irritation of the gastrointestinal tract. Based on the acute oral LD50, this product is considered practically non-toxic by ingestion.

Chronic Effects: A study was conducted where groups of rats were exposed for 6 hours/day, 5 days/week for a lifetime to atmospheres of respirable polymeric MDI aerosol either at concentrations of 0, 0.2, 1 or 6 mg/m³. No adverse effects were observed at 0.2 mg/m³ concentrations. At the 1 mg/m³ concentration minimal nasal and lung irritant effects were seen. Only at the top concentration (6.0 mg/m³) there was an increased incidence of a benign tumor of the lung (adenoma) and one malignant tumor (adenocarcinoma). Overall, the tumor incidence, both benign and malignant, and the number of animals with tumors were not different. The increased incidence of lung tumors is associated with prolonged respiratory irritation and the concurrent accumulation of yellow material in the lung. In the absence of prolonged exposure to high concentrations leading to chronic irritation and lung damage, it is highly unlikely that tumor formation will occur.

There are reports that excessive chronic exposure to diisocyanates may result in permanent decrease in lung function.

Carcinogenicity: The ingredients of this product are not classified as carcinogenic by ACGIH or IARC, not regulated as carcinogens by OSHA, and not listed as carcinogens by NTP.

Mutagenicity: There is no substantial evidence of mutagenic potential.

Reproductive Effects: No adverse reproductive effects are anticipated.

Teratogenicity and Fetotoxicity: No birth defects were seen in two independent animal (rat) studies. Fetotoxicity was observed at doses that were extremely toxic (including lethal) to the mother. Fetotoxicity was not observed at doses that were not maternally toxic. The doses used in these studies were maximal, respirable concentrations well in excess of the defined occupational limits.

SECTION XII: ECOLOGICAL INFORMATION

Environmental Fate and Distribution: It is unlikely that significant environmental exposure in the air or water will arise, based on consideration of the production and use of the substance.

Persistence and Degradation: Immiscible with water, but will react with water to produce inert and non-biodegradable solids.

Toxicity: Polymeric MDI.

LC50 (Zebra Fish) > 1000 mg/l (at the highest level teste of 1000 mg/l there were no deaths)

EC50 (daphnia magna) (24 hour) > 1000 mg/l

EC50 (E. Coli) > 100 mg/l

SECTION XIII: DISPOSAL CONSIDERATIONS

The generation of waste should be avoided or minimized whenever possible.

Disposal should be in accordance with local, state, provincial or national regulations. This material is not a hazardous waste under RCRA 40 CFR 261. Small quantities should be treated with a decontaminant solution (see SECTION VI). The treated waste is not a hazardous material under RCRA 40 CFR 261. Chemical waste, even small quantities, should never be poured down drains, sewers or waterways.

Empty containers should be decontaminated and either passed to an approved drum recycler or destroyed.

SECTION XIV: TRANSPORT INFORMATION

DOT: Single containers less than 5,000 lbs. are not regulated. Single containers with 5,000 lbs. or more of 4,4'-MDI are regulated as: Other Regulated Substances, Liquid, N.O.S. (Methylene Diphenyl Diisocyanate), 9, NA3082, PGIII, RQ.

TDG: Not regulated.

IMO: Not regulated.

IATA/ICAO Class: Not regulated.

SECTION XV: REGULATORY INFORMATION

USA CLASSIFICATION:

OSHA Classification: This product is classified as a hazardous material under the criteria outlined in the OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200).

TSCA (Toxic Substances Control Act) Regulations: All ingredients are on the TSCA Chemical Substance Inventory.

EPCRA Section 313 (40 CFR 372): This product contains the following chemical(s) subject to reporting requirements: 100% Diisocyanate compounds (Category Code N120).

CERCLA (Comprehensive Environmental Response, Compensation and Liability Act): 4,4'-Methylene diphenyl diisocyanate (CAS 101-68-8) has a 5,000 lb. RQ (reportable quantity). Any spill or release above the RQ must be reported to the National Response Center (800-424-8802). The % of 4,4'-MDI in this product is listed in Section II of this MSDS.

This produce does not contain nor is it manufactured with ozone depleting substances.

Other Regulations/Legislation which apply to this product: Massachusetts Right-to-Know. Pennsylvania Right-to-Know, New Jersey Right-to-Know, CERCLA.

CANADIAN CLASSIFICATION

This product has been classified in accordance with the hazard criteria of the CPR (Controlled Products Regulations) and this MSDS (Material Safety Data Sheet) contains all the information required by the CPR.

Controlled Products Regulations (WHMIS) Classification: D-1A; D-2A and D-2B.

CEPA/Canadian Domestic Substances List (DSL): The substance(s) in this product is/are on the Canadian Domestic Substances List (CEPA DSL).

SECTION XVI: OTHER INFORMATION

Glossary: ACGIH - American Conference of Governmental Industrial Hygienists
IARC - International Agency for Research on Cancer
NTP - National Toxicology Program
OSHA- Occupational Safety and Health Administration

For Your Protection: The information and recommendations in the publication are, to the best of our knowledge, reliable. The toxicity and risk characteristics of products made by Motion Picture F/X Company will necessarily differ from the toxicity and risk characteristics that occur when such products are used with other materials during a manufacturing process. The resulting risk characteristics should be determined and made known to ultimate end-users and processors. MOTION PICTURE F/X COMPANY MAKES NO GUARANTY, WARRANTY, OR REPRESENTATION AS TO THE CORRECTNESS, OR SUFFICIENCY OF ANY INFORMATION, OR AS TO THE MERCHANTABILITY OR SUITABILITY OR FITNESS OF ANY CHEMICAL COMPOUNDS OR OTHER PRODUCTS FOR ANY PARTICULAR USE OR PURPOSE, OR THAT ANY CHEMICAL COMPOUNDS OR OTHER PRODUCTS OR THE USE THEREOF ARE NOT SUBJECT TO A CLAIM BY A THIRD PARTY FOR INFRINGEMENT OF ANY PATENT OR OTHER INTELLECTUAL PROPERTY RIGHT. THE USER SHOULD CONDUCT SUFFICIENT INVESTIGATION TO ESTABLISH THE SUITABILITY OF ANY PRODUCT FOR ITS INTENDED USE.