

MATERIAL SAFETY DATA SHEET

SECTION I: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: **BALDFX CLEAR PRE-MIX**
PRODUCT USE: Manufacture (coating) of custom prostheses and creation of Bald Caps

COMPANY: Motion Picture F/X Company
2920 W. Magnolia Blvd Burbank, CA 91505
(818) 563-2366 (Tel)
(818) 563-2389 (Fax)
info@motionpicturefx.com

EMERGENCY PHONE: In the event of a leak, fire or medical emergency involving humans and animals call **INFOTRAC 1-800-535-5053** 24 hours per day, 7 days a week. or +1-352-323-3500 (outside the us)

SECTION II: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Nature Dispersion of dissolved polymer in organic solvent

Hazardous Components Acetone (synonyms: dimethyl ketone, 2-proprnonr)
85% acetone by weight.

SECTION III: HAZARDS IDENTIFICATION

Critical Hazards In "wet" state: highly flammable, irritating to eyes, vapors may cause drowsiness/dizziness

SECTION IV: FIRST AID MEASURES

Inhalation: Remove patient from exposure, keep warm and at rest. In severe case, or if exposure is great/prolonged, obtain medical attention.

Skin Contact: Remove excess and drench with water, Remove contaminated clothing.

Eye Contact: Immediately flush eyes with running water for a minimum of 15 minutes. Hold eyelids open during flushing. If irritation persists, repeat flushing. Obtain medical attention IMMEDIATELY.

Ingestion: Drink plenty of water, seek medical advice.

SECTION V: FIRE-FIGHTING MEASURES

Hazards during fire fighting: Highly flammable. Dense vapor/air mixture explosive.
Vapor heavier than air.

Extinguishing Media: Water, foam, Carbon dioxide, dry chemical. Cool container with
Water at a distance

SECTION VI: ACCIDENTAL RELEASE MEASURES

Personal Protection. Refer to Section VIII.

Environmental Precautions. Shut off all sources of ignition. Do Not wash away
into any drain unless it drains into suitable
effluent treatment process.

Methods for clean-up Soak up with an inert absorbent (eg. Sand) and
dispose as Section XIII.

SECTION VII: HANDLING AND STORAGE

Handling: Work in well ventilated area. Observe good
housekeeping practices.

Storage Store between 15 deg C and 25 deg C in Chemical
storage cabinet. Keep lid well sealed to avoid flash
off of solvent.

SECTION VIII: EXPOSURE CONTROLS/PERSONAL PROTECTION

General Protective Measures Well ventilated work area to prevent build up of
Fumes.

Components with workplace parameters OES Acetone (long term 500 ppm, short term 1,500
ppm (IOELV)

Respiratory Protection Mask if spraying

Hand Protection Gloves recommended

Eye Protection Eye glasses recommended

Other Precautions Apron, sleeves, boots recommended if handling
large quantities

Hygiene Measures Do not eat, drink or smoke when handling product.

SECTION IV: PHYSICAL AND CHEMICAL PROPERTIES

Physical Form	Thick, viscous liquid liquid.
Color	Amber
Odor:	Characteristic
PH:	Approx 5.0-6.0 (400g/l, water, 20 deg C)
Flash Point:	< -20 deg C
Vapor Pressure	233 hPa (20deg C)
Boiling Point:	Approx 56 deg C
Auto ignition temperature	380 deg C.
Explosion limits	lower: 2.6% v/v, upper: 13% v/v

SECTION X: STABILITY AND REACTIVITY

The product is stable under normal storage conditions (refer to Section VII)

Incompatible materials	Oxidizing agents. The possibility of reaction with other substances cannot be excluded
-------------------------------	--

SECTION XI: TOXICOLOGICAL INFORMATION

Treat as if Acetone.

After Inhalation:	Mucosal irritation. In high doses, headache, salivation, nausea, vomiting, dizziness, narcosis, coma
After Skin Contact:	Degreasing effect on skin, possibly followed by secondary inflammation
After Eye Contact:	Risk of corneal clouding
After Ingestion:	gastrointestinal complaints
Oder threshold	approx 13 ppm

We have no evidence of carcinogenic, mutagenic or teratogenic effects

SECTION XII: ECOLOGICAL INFORMATION

Degradation/elimination	Good
Bioaccumulation potential	Low
Ecotoxic effects	This product is not classified as Dangerous to the Environment when handled and disposed of carefully.

SECTION XIII: DISPOSAL CONSIDERATIONS

Chemical waste, even small quantities, should never be poured down drains, sewers or waterways.

Disposal should be in accordance with local, state, provincial or national regulations.

SECTION XIV: TRANSPORT INFORMATION

Transport as if Acetone.

UN number 1090-ACETONE

Class 3

Packaging group II

SECTION XV: REGULATORY INFORMATION

Transport as if Acetone.

Risk and safety phrases: Highly flammable.
Keep container in cool, well ventilated place.
Keep away from sources of ignition. NO SMOKING

For Your Protection: The information and recommendations in the publication are, to the best of our knowledge, reliable. The toxicity and risk characteristics of products made by Motion Picture F/X Company will necessarily differ from the toxicity and risk characteristics that occur when such products are used with other materials during a manufacturing process. The resulting risk characteristics should be determined and made known to ultimate end-users and processors. MOTION PICTURE F/X COMPANY MAKES NO GUARANTY, WARRANTY, OR REPRESENTATION AS TO THE CORRECTNESS, OR SUFFICIENCY OF ANY INFORMATION, OR AS TO THE MERCHANTABILITY OR SUITABILITY OR FITNESS OF ANY CHEMICAL COMPOUNDS OR OTHER PRODUCTS FOR ANY PARTICULAR USE OR PURPOSE, OR THAT ANY CHEMICAL COMPOUNDS OR OTHER PRODUCTS OR THE USE THEREOF ARE NOT SUBJECT TO A CLAIM BY A THIRD PARTY FOR INFRINGEMENT OF ANY PATENT OR OTHER INTELLECTUAL PROPERTY RIGHT. THE USER SHOULD CONDUCT SUFFICIENT INVESTIGATION TO ESTABLISH THE SUITABILITY OF ANY PRODUCT FOR ITS INTENDED USE.